HG RACK 2U BASIC (SX 3080)

PEM Rack 19 inch Hydrogen generator

The HydroGen series **HG RACK 19" 2U BASIC** is able to generate up to 600 cc/min of Hydrogen with purity better than 99.9999% and pressure up to 10 bar (145 psi). The **HG 2U 19 inch BASIC** includes a new long life multilayer electrolytic cell with polymeric membrane (PEM) using distilled water. No acid or alkaline solutions are used.

The innovative drying system ensures the maximum grade of hydrogen purity, protects the GC thanks to its innovative humidity safe guard, HG 19 inch 2U BASIC is completely maintenance-free and allows continuous operation, 24 hours a day.

The on-board CPU automatically checks for internal leaks and constantly controls the operating parameters to guarantee full safety. Up to 20 units can be connected in parallel mode using an external control box.

The touch-screen LCD interface provides simple and user-friendly management of all functions on the unit.

Main Applications

- GC-FID / GC-NPD / GC-FPD
- THA

Main Advantages

- Quick installation
- ✓ Easy use
- ✓ Hydrogen flow rate up to 600 cc/min
- ✔ Pressure up to 10 bar (145 psi)
- ✔ Hydrogen purity: 99.9999%
- RS 485 and USB as standard
- ✓ LAN optional
- ✔ Dryer with no maintenance
- ✔ Reduced foot print: 19 inch rack 2U
- ✓ Smart humidity safe guard (patented)
- ✓ High pressure GLS electronically controlled (patented)









Models: HG 2U BASIC	100	160	250	350	600
General data					
Electrolytic cell	PEM technology				
Drying system	Static dryer				
H2 purity	>99.9999% *1				
Outlet pressure	10 bars (145 psi)				
H2 flow-rate cc/min (Max)	100	160	250	350	600
Dimensions		Standard	I 2U RACK (48 c	m deep)	
Net weight (no water in tank)	15 kg				
Communication					
RS485/USB	Standard				
LAN	Optional				
Software functions					
Parallel mode	Ready on board				
Automatic tank refill	Standard				
Water					
Quality	Deionized, ASTM II, <0.1uS				
Supply pressure (min, Max)		0 bars (0 psi), 0.5 bar (7.25 psi)			
Internal tank capacity		0.3			
Electrical data					
Type of connection		IEC 320-C14			
Power supply voltage	100-240 Vac (±10%) 50/60 Hz				
Nominal power (Max)		350W		500W	
Fuse rating (5x 20 mm)		4A (250VAC – T)			
Connections					
Hydrogen outlet		1/8" compression fitting			
Water (inlet, drain)		Quick release push-in fitting			

^{*1} Referred to O₂ - DewPoint < -25°C (<-13°F), Atmospheric Dew Point (ADP)

Ordering codes	
Gas Generators	
6920.11.010	HG 2U BASIC 100
6920.11.016	HG 2U BASIC 160
6920.11.025	HG 2U BASIC 250
6920.11.035	HG 2U BASIC 350
6920.11.060	HG 2U BASIC 600
Consumable	
6930.00.091	Deionizer water filter

