

NGA CASTORE XL iQ SCIEX 7500

Membrane Nitrogen generator with
integrated direct drive Scroll compressor.
Electronic controlled

NGA CASTORE XL iQ SCIEX 7500 is a Nitrogen Generator with Membrane technology.

It is engineered to transform standard compressed air into a supply of Nitrogen up to 26 L/min and with two additional outlets for dry and clean air. All of these three outlets have its own internal flow/pressure regulator for an appropriate adjustment to guarantee safety and precision.

The CASTORE XL iQ SCIEX 7500 with its dual Nitrogen and Air outlets has been developed to meet specific requirements in term of gas, flow, purity and pressure for SCIEX triple quad 7500.

A special carbon filter is used to remove VOC.

It can be used for LC-MS and the evaporation of solvents in samples being analysed.

The new **iQ** generators are equipped with an innovative direct drive motor-scroll compressor system (oil less) with inverter technology.

The exclusive electronic flow control combined with the compressor control by the inverter allows to generate Nitrogen with a higher purity using a smaller volume at less pressure of air which results in reduced energy costs and increase the life time of the compressor. Continuous control of the operating parameters of Nitrogen allows to maintain the system at its maximum efficiency.

Main applications

- SCIEX instruments
- Solvent evaporation
- LCMS

Main advantages

- ✓ Compatible with SCIEX triple quad 7500
- ✓ Carbon filter to remove VOC
- ✓ Dual Nitrogen and Air generator
- ✓ Plug & Play
- ✓ Low noise
- ✓ Low maintenance
- ✓ No belts, direct drive
- ✓ Generates nitrogen on demand
- ✓ Exclusive electronic flow control with automatic Stand-by function
- ✓ Ultra silent technology: 50 dB(A)
- ✓ Reliable – No vibrations
- ✓ Designed to run 24 hours a day



Specifications



Models: NGA CASTORE XL iQ	SCIEX 7500	
	6920.70.44	6920.70.44.1
N2 outlet		
Flow rate (Max)	32 L/min	
Outlet pressure	4.5 bar (65 psi)	
N2 purity	LCMS grade (up to 99.9%)	
Dew point *1	< -60°C (<-76°F)	
Dry Air outlet 1 (Gas 1/ Gas 2 / Bath gas)		
Flow rate (Max)	26 l/min	
Outlet pressure (Max)	7.25 Bar (105 psi)	
Dew point *1	< -40°C (<-40°F)	
Dry Air outlet 2		
Flow rate (Max)	25 l/min	
Outlet pressure (Max)	7.25 Bar (105 psi)	
Dew point *1	< -40°C (<-40°F)	
Communication		
LCD with touch screen	Standard	
RS485	Standard	
RS232	For service	
WiFi	Optional	
General data		
Power supply voltage (min..Max)	220-240 Vac (±10%) 50/60 HZ	115-240 Vac (±10%) 50/60 HZ
Connection type	IEC C20	
Rated power	1.9 kW	1.7 kW
Net weight	180 kg	190 kg
Noise level	< 50 dB	
Heat value (BTU)	6500	5800
Dimensions (W x D x H)	59 x 92 x 73 cm	
Connections		
N2 outlet port	¼" SWAGELOK compatible	
Dry Air outlet port	¼" SWAGELOK compatible	
Drain port	¼" BSPP female	
Operating/storage conditions		
Temperature	5-35°C (41-95°F) *2	
Humidity (max, non condensing)	80% [5-35°C (41-95°F)]	
Altitude	< 2000 m	
Pollution degree rating	2 (with no aromatic compounds)	
IP rating	IP20	

*1 – Atmospheric Dew Point (ADP)

*2 – Min temperature > 10°C to have best performance on O₂ residual content

Ordering codes

Gas Generators

6920.70.44 NGA CASTORE XL iQ SCIEX 7500 **(220-240 Vac models)**

6920.70.44.1 NGA CASTORE XL iQ SCIEX 7500 **(115-240 Vac models)**
FULL RANGE power supply voltage

Options

6920.71.50 WiFi Module for CASTORE XL
6920.50.012 O₂ sensor option (%) for CASTORE XL
6920.71.80 Carbon column for NG CASTORE XL

Consumable

6930.00.141 Filter elements for NG CASTORE XL without carbon column installed
6930.00.148 Filter elements for NG CASTORE XL with carbon column installed
6930.00.147 Carbon filter column for NG CASTORE XL



LNI Swissgas
www.lni-swissgas.eu

LNI Swissgas Srl
Registered office: Via Sassoferato 1, 20135 Milano MI
Logistics centre: Via E. Mattei 9, 35038 Torreglia PD