

KEY FEATURES

- 3.7 LITERS PER MINUTE OF 18 MEGOHM WATER
- AUTOMATICALLY FILL ANY SIZE CONTAINER
- COUNTER SPACE SAVING WALL MOUNTED DESIGN

GEMINI-MB SYSTEM

The GEMINI-MB Ultra High Purity Water System provides 3.7 liters per minute of 18.2 megohm, 0.2 micron filtered water.* The Multi-Pass Ultraviolet system irradiates the water at three separate passes in the recirculation loop. The dispensing port is continuously exposed to UV for complete sterility at the outlet. Water quality meets or exceeds ASTM, CAP and NCCLS Type 1 specifications.

Controls include PLC and a 3.5" high resolution HMI display. Touch panel screen provides easy interface for dispensing and programming up to four batches. Resistivity is clearly displayed with system operation status. Display turns red during alarm condition below resistivity set point. Hibernation mode runs the pump intermittently to keep the system ultrapure.

The convenient wall mount design accommodates filling large containers. A variety of options are available such as a dispensing gun, ultra-filtration, wall mounting hardware and a sanitization kit. RO pretreatment systems are also available.

*Note: Reported flow rate is typical but can vary depending on supply pressure and system options.




FEATURES & BENEFITS

- **MICROPROCESSOR CONTROLLED**
Intuitive touch screen allows for programmable dispensing of 18.2 megohm water into various containers at the touch of a button.
- **MULTI-PASS UV STERILIZATION**
Continuous recirculation ensures water quality is maintained before it passing through the UV sterilized dispensing port.
- **ULTRAPURE WATER**
Exceeds ASTM, CAP and NCCLS Type I specifications and meets bio-medical grade specification ASTM D5196.

Note: Flow rate may vary depending on supply pressure and/or system options.

FLOW DIAGRAM



GEMINI-MB ULTRA HIGH-PURITY WATER SYSTEM

TECHNICAL DATA



Dimensions (H x W x D)

21.5 in. x 18.25 in. x 17 in.
(61 cm x 46 cm x 43 cm)

Weight

42 lbs. dry / 47 lbs operating
(22.7 kg dry / 25 kg operating)

Inlet Connection

3/8" O.D. Tubing
.375 mm O.D. Tubing

Power Requirements

120 VAC/ 60 Hz @ 1.0 amp

Pressure

90 PSIG Maximum
20 PSIG Minimum

Temperature (Max.)

100 °F
30 °C

Flow Rate (Typical)

1.0 Gallons Per Minute
3.7 Liters Per Minute

Outer Shell

Polypropylene
316 Stainless Steel

INFLUENT QUALITY

Source	Reverse Osmosis, DI, or Distillation
Purity	< 20 μ S/cm
Filtration	0.2 μ m
Free Chlorine	< 0.05 ppm
Silica	< 2 ppm
TOC	< 50 ppb

EFFLUENT QUALITY (STANDARD SYSTEM)

Standard System-	
Purity	> 18 Megohm-cm
Microorganisms	< 10 CFU / 1000 ml
Chlorides	< 1 ppb
Sodium	< 1 ppb
With 0.05 micron UF- Endotoxin	< 0.03 EU
With Combination UV / TOC Destruct- TOC	< 3 ppb

ORDERING GUIDE

GMB-102	110 VAC Unit w/ 0.2 μ Filter
GMB-105	110 VAC Unit w/ 0.05 μ m Ultra Filter

OPTIONS & ACCESSORIES

GMA-DG	Dispensing gun and tubing kit
GMA-UV	U.V. Combination for bacteria and TOC destruct
GMA-DF	Direct feed
GMA-WB	Wall mounting bracket
AFK-002	Cartridge Kit w/ (2) high purity cartridges
AFK-006	Cartridge Kit with (2) low TOC Deionization Cartridges and 10-inch 0.2 micron filter
AFK-008	Cartridge Kit with (3) high purity Low TOC Cartridges and (1) 0.05 μ ultrafilter
AFK-009	Cartridge Kit with (3) high purity Low TOC Cartridges
PF-00-6505	In-Line Hollow Fiber 0.05 micron UF for pyrogen removal
HPA-005	Sanitization Kit
HPA-008	220 VAC external power converter
HPL-RO	Reverse Osmosis pretreatment

MADE IN USA

WE ARE PROUD TO BE
ISO 9001 : 2015 CERTIFIED



Note: Ordering information subject to change without notice. Please verify all specifications prior to ordering.
For more information Call: (856) 626-1550.

IMPORTANT NOTICE TO USER:

The following is made in lieu of all other warranties expressed or implied. Manufacturer's and Seller's only obligation shall be to issue credit against the purchase or replacement of the equipment proved to be defective in material or workmanship. Neither Manufacturer nor Seller shall be liable for any injury, loss or damage, direct or indirect, special or consequential, arising out of the use of, misuse, or the inability to use such product. The information contained herein is based on technical data and tests which we believe to be reliable and is intended for use by persons having technical skill at their discretion and risk. Since conditions of use are outside ResinTech's control, we can assume no liability whatsoever for results obtained or damages incurred through the application of the data presented. This information is not intended as a license to operate under, or a recommendation to infringe upon, any patent of ResinTech's or others covering any material or use. The foregoing may not be altered except by written agreement signed by officers of the manufacturer.

DS-GeminiMB 1.2